

Fiber Optic Transceiver, SFP, CWDM, EZX SMF  
120KM, 1000Base DDM, Ciena Compliant



## FXC-SFP-CxxEZX1G-CAN

### Features

- Operating Data Rate up to 1.25 Gbps
- Distance Range 120KM
- Pluggable SFP- Duplex LC Connectors
- Standard and Industrial Operating Temperature
- Compliant with Ciena Specification

### Applications

- Telecom ( Service Providers)
- Datacom
- Enterprise Networks
- Government
- Fiber to the home / business

### Description

The L-com FXC-SFP-CxxEZX1G-CAN series are SFP transceivers, supporting 1G Ethernet data rates. The SFP CWDM series transceivers have CWDM transmitters, with operating wavelengths between 1470 nm to 1610 nm. The L-com FXC-SFP-CxxEZX1G-CAN series support 120KM distance and are compliant with Ciena system level specifications. The L-com FXC-SFP-CxxEZX1G-CAN series feature digital diagnostics for performance monitoring of the transceivers. The L-com FXC-SFP-CxxEZX1G-CAN series are one of thousands of fiber optic connectivity products available from L-com's in-stock inventory and ready to ship. Contact our knowledgeable technical support and sales staff with your questions on fiber optic connectivity or other L-com products.

### Configuration

|                            |             |
|----------------------------|-------------|
| Data Rate                  | 1.25 Gbps   |
| Form Factor                | SFP         |
| Connector                  | LC          |
| Connector Mode             | Duplex      |
| Mode                       | Single Mode |
| Distance                   | 120 km      |
| Mfg Platform Compatibility | Ciena       |

### Electrical Specifications

| Description          | Minimum | Typical | Maximum | Units |
|----------------------|---------|---------|---------|-------|
| Power Supply Voltage | 3.15    | 3.3     | 3.45    | V     |
| Power Supply Current |         |         | 300     | mA    |
| Module Total Power   |         |         | 1       | W     |

### Optical Specifications

| Description             | Minimum         | Typical     | Maximum           | Units |
|-------------------------|-----------------|-------------|-------------------|-------|
| TX Center Wavelength*   | $\lambda_c - 6$ | $\lambda_c$ | $\lambda_c + 7.5$ | nm    |
| TX Data Rate            | 1.06            |             | 1.25              | Gbps  |
| TX Average Output Power | 0               |             | 5                 | dBm   |
| TX Extinction Ratio     | 8.2             |             |                   | dB    |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[FXC-SFP-CxxEZX1G-CAN](#)

Fiber Optic Transceiver, SFP, CWDM, EZX SMF  
120KM, 1000Base DDM, Ciena Compliant



## FXC-SFP-CxxEZX1G-CAN

|                         |      |      |     |
|-------------------------|------|------|-----|
| RX Center Wavelength    | 1260 | 1620 | nm  |
| RX Receiver Sensitivity |      | -34  | dBm |
| RX Receiver Overload    | -10  |      | dBm |

\*See table below

### Wavelength Channel No.

| ITU<br>Channel No. | Wavelength | Latch color by wavelength |
|--------------------|------------|---------------------------|
| (xx)               | nm         |                           |
| 47                 | 1471       |                           |
| 49                 | 1491       |                           |
| 51                 | 1511       |                           |
| 53                 | 1531       |                           |
| 55                 | 1551       |                           |
| 57                 | 1571       |                           |
| 59                 | 1591       |                           |
| 61                 | 1611       |                           |

### Environmental Specifications

#### Temperature

Operating Range

0 to +70 deg C

Storage Range

-40 to +85 deg C

Fiber Optic Transceiver, SFP, CWDM, EZX SMF  
120KM, 1000Base DDM, Ciena Compliant



## FXC-SFP-CxxEZX1G-CAN


Notes:

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:


### Small Form-factor Pluggable (SFP) Transceiver MultiSource Agreement (MSA)



Fiber Optic Transceiver, SFP, CWDM, EZX SMF  
120KM, 1000Base DDM, Ciena Compliant



## FXC-SFP-CxxEZX1G-CAN



**Figure 1. Diagram of Host Board Connector Block Pin Numbers and Names**

Fiber Optic Transceiver, SFP, CWDM, EZX SMF 120KM, 1000Base DDM, Ciena Compliant from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

